

BISPHENOL A

InterAtlas Chemical Inc.

Chemwatch Hazard Alert Code: 3

Chemwatch: 23320
Version No: 11.1.15.12
Safety Data Sheet according to OSHA HazCom Standard (2012) requirements

Issue Date: 15/04/2021
Print Date: 30/09/2021
S.GHS.USA.EN

SECTION 1 Identification

Product Identifier

| | |
|-------------------------------|---|
| Product name | BISPHENOL A |
| Chemical Name | bisphenol A |
| Synonyms | C15-H16-O2; HOC6H4C(CH3)2C6H4OH; phenol, 4,4'-isopropylidenedi-; dimethyl bis(p-hydroxyphenyl)methane; bis(4-hydroxyphenyl)dimethylmethane; diphenylolpropane; bis(4-hydroxyphenyl)propane; 2,2-di(4-phenylol)propane; 2,2-bis(p-hydroxyphenyl)propane; p,p'-isopropylidenebisphenol; 2,2-bis(4-hydroxyphenyl)propane; 4,4'-isopropylidenebisphenol; 4,4'-bisphenol A; p,p'-bisphenol A; p,p'-isopropylidenediphenol; p,p'-dihydroxydiphenylmethane; 4,4'-isopropylidenediphenol; 4,4'-dihydroxydiphenylmethane; phenol, 4,4'-dimethylmethylenedi-; p,p'-dihydroxydiphenylpropane; 2,2-(4,4'-dihydroxydiphenyl)propane; 4,4'-dihydroxydiphenylpropane; 4,4'-dihydroxydiphenyl-2,2-propane; 4,4'-dihydroxy-2,2'-diphenylpropane; dimethylmethylenep,p'-diphenol; beta-di-p-hydroxyphenylpropane; 2,2-di(4-hydroxyphenyl)propane; 4,4'-(1-methylethylidene)bisphenol; Shell Diphenylol Propane 00499 H712; Dian Diano Parabis A Puracol 245 Hidorin F-285 Rikabanol; Ipognon 80 |
| Proper shipping name | Environmentally hazardous substance, solid, n.o.s. (contains bisphenol A) |
| Chemical formula | C15H16O2 |
| Other means of identification | Not Available |
| CAS number | 80-05-7 |

Recommended use of the chemical and restrictions on use

| | |
|--------------------------|---|
| Relevant identified uses | In manufacture of epoxy, polycarbonate, phenoxy, polysulphone and certain polyester resins, flame retardants, rubber chemicals, fungicide. [-Fragrance -] Intermediate. |
|--------------------------|---|

Name, address, and telephone number of the chemical manufacturer, importer, or other responsible party

| | |
|-------------------------|--|
| Registered company name | InterAtlas Chemical Inc. |
| Address | 63 Church Street, Suite 301, St. Catharines Ontario L2R 3C4 Canada |
| Telephone | 905-684-9991 |
| Fax | 905-684-4504 |
| Website | www.interatlaschemical.com |
| Email | Not Available |


Emergency phone number

| | |
|-----------------------------------|--------------------------------|
| Association / Organisation | CHEMTREC, US |
| Emergency telephone numbers | 800-424-9300 |
| Other emergency telephone numbers | International: +1-703-527-3887 |

SECTION 2 Hazard(s) identification

Classification of the substance or mixture

NFPA 704 diamond



Note: The hazard category numbers found in GHS classification in section 2 of this SDSs are NOT to be used to fill in the NFPA 704 diamond. Blue = Health Red = Fire Yellow = Reactivity White = Special (Oxidizer or water reactive substances)

| | |
|----------------|---|
| Classification | Serious Eye Damage/Eye Irritation Category 1, Sensitisation (Skin) Category 1, Reproductive Toxicity Category 2, Specific Target Organ Toxicity - Single Exposure (Respiratory Tract Irritation) Category 3, Hazardous to the Aquatic Environment Long-Term Hazard Category 2 |
|----------------|---|

Label elements

| | |
|---------------------|---|
| Hazard pictogram(s) |  |
|---------------------|---|

| | |
|-------------|---------------|
| Signal word | Danger |
|-------------|---------------|

Hazard statement(s)

| | |
|------|--|
| H318 | Causes serious eye damage. |
| H317 | May cause an allergic skin reaction. |
| H361 | Suspected of damaging fertility or the unborn child. |
| H335 | May cause respiratory irritation. |
| H411 | Toxic to aquatic life with long lasting effects. |

Hazard(s) not otherwise classified

Not Applicable

Precautionary statement(s) Prevention

| | |
|------|--|
| P201 | Obtain special instructions before use. |
| P271 | Use only outdoors or in a well-ventilated area. |
| P280 | Wear protective gloves, protective clothing, eye protection and face protection. |
| P261 | Avoid breathing dust/fumes. |
| P273 | Avoid release to the environment. |
| P202 | Do not handle until all safety precautions have been read and understood. |
| P272 | Contaminated work clothing must not be allowed out of the workplace. |

Precautionary statement(s) Response

| | |
|----------------|--|
| P305+P351+P338 | IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. |
| P308+P313 | IF exposed or concerned: Get medical advice/ attention. |
| P310 | Immediately call a POISON CENTER/doctor/physician/first aider. |
| P302+P352 | IF ON SKIN: Wash with plenty of water and soap. |
| P312 | Call a POISON CENTER/doctor/physician/first aider/if you feel unwell. |
| P333+P313 | If skin irritation or rash occurs: Get medical advice/attention. |
| P362+P364 | Take off contaminated clothing and wash it before reuse. |
| P391 | Collect spillage. |
| P304+P340 | IF INHALED: Remove person to fresh air and keep comfortable for breathing. |

Precautionary statement(s) Storage

| | |
|-----------|--|
| P405 | Store locked up. |
| P403+P233 | Store in a well-ventilated place. Keep container tightly closed. |

Precautionary statement(s) Disposal

| | |
|------|--|
| P501 | Dispose of contents/container to authorised hazardous or special waste collection point in accordance with any local regulation. |
|------|--|

SECTION 3 Composition / information on ingredients

Substances

| CAS No | %[weight] | Name |
|----------|-----------|--|
| 80-05-7 | >97 | <u>bisphenol A</u> |
| 837-08-1 | 2 | <u>2,4'-(1-methylethylidene)phenol</u> |
| 108-95-2 | 0.2 | <u>phenol</u> |

Mixtures

See section above for composition of Substances

SECTION 4 First-aid measures

Description of first aid measures

| | |
|-------------|---|
| Eye Contact | <p>If this product comes in contact with the eyes:</p> <ul style="list-style-type: none"> ▶ Immediately hold eyelids apart and flush the eye continuously with running water. ▶ Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids. ▶ Continue flushing until advised to stop by the Poisons Information Centre or a doctor, or for at least 15 minutes. ▶ Transport to hospital or doctor without delay. |
|-------------|---|

| | |
|---------------------|--|
| | <ul style="list-style-type: none"> ▶ Removal of contact lenses after an eye injury should only be undertaken by skilled personnel. |
| Skin Contact | <p>If skin contact occurs:</p> <ul style="list-style-type: none"> ▶ Immediately remove all contaminated clothing, including footwear. ▶ Flush skin and hair with running water (and soap if available). ▶ Seek medical attention in event of irritation. |
| Inhalation | <ul style="list-style-type: none"> ▶ If fumes or combustion products are inhaled remove from contaminated area. ▶ Lay patient down. Keep warm and rested. ▶ Prostheses such as false teeth, which may block airway, should be removed, where possible, prior to initiating first aid procedures. ▶ Apply artificial respiration if not breathing, preferably with a demand valve resuscitator, bag-valve mask device, or pocket mask as trained. Perform CPR if necessary. ▶ Transport to hospital, or doctor, without delay. |
| Ingestion | <ul style="list-style-type: none"> ▶ Immediately give a glass of water. ▶ First aid is not generally required. If in doubt, contact a Poisons Information Centre or a doctor. |

Most important symptoms and effects, both acute and delayed

See Section 11

Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

As in all cases of suspected poisoning, follow the ABCDEs of emergency medicine (airway, breathing, circulation, disability, exposure), then the ABCDEs of toxicology (antidotes, basics, change absorption, change distribution, change elimination).

For poisons (where specific treatment regime is absent):

BASIC TREATMENT

- ▶ Establish a patent airway with suction where necessary.
- ▶ Watch for signs of respiratory insufficiency and assist ventilation as necessary.
- ▶ Administer oxygen by non-rebreather mask at 10 to 15 L/min.
- ▶ Monitor and treat, where necessary, for pulmonary oedema.
- ▶ Monitor and treat, where necessary, for shock.
- ▶ Anticipate seizures.
- ▶ **DO NOT** use emetics. Where ingestion is suspected rinse mouth and give up to 200 ml water (5 ml/kg recommended) for dilution where patient is able to swallow, has a strong gag reflex and does not drool.

ADVANCED TREATMENT

- ▶ Consider orotracheal or nasotracheal intubation for airway control in unconscious patient or where respiratory arrest has occurred.
- ▶ Positive-pressure ventilation using a bag-valve mask might be of use.
- ▶ Monitor and treat, where necessary, for arrhythmias.
- ▶ Start an IV D5W TKO. If signs of hypovolaemia are present use lactated Ringers solution. Fluid overload might create complications.
- ▶ Drug therapy should be considered for pulmonary oedema.
- ▶ Hypotension with signs of hypovolaemia requires the cautious administration of fluids. Fluid overload might create complications.
- ▶ Treat seizures with diazepam.
- ▶ Proparacaine hydrochloride should be used to assist eye irrigation.

BRONSTEIN, A.C. and CURRANCE, P.L.

EMERGENCY CARE FOR HAZARDOUS MATERIALS EXPOSURE: 2nd Ed. 1994

SECTION 5 Fire-fighting measures

Extinguishing media

- ▶ Foam.
- ▶ Dry chemical powder.
- ▶ BCF (where regulations permit).
- ▶ Carbon dioxide.
- ▶ Water spray or fog - Large fires only.

Special hazards arising from the substrate or mixture

| | |
|-----------------------------|--|
| Fire Incompatibility | ▶ Avoid contamination with oxidising agents i.e. nitrates, oxidising acids, chlorine bleaches, pool chlorine etc. as ignition may result |
|-----------------------------|--|

Special protective equipment and precautions for fire-fighters

| | |
|------------------------------|---|
| Fire Fighting | <ul style="list-style-type: none"> ▶ Alert Fire Brigade and tell them location and nature of hazard. ▶ Wear breathing apparatus plus protective gloves. ▶ Prevent, by any means available, spillage from entering drains or water courses. ▶ Use water delivered as a fine spray to control fire and cool adjacent area. ▶ DO NOT approach containers suspected to be hot. ▶ Cool fire exposed containers with water spray from a protected location. ▶ If safe to do so, remove containers from path of fire. ▶ Equipment should be thoroughly decontaminated after use. |
| Fire/Explosion Hazard | <p>Bisphenol A dust constant of 297 bar m/sec. Classified in the explosion class 3.</p> <ul style="list-style-type: none"> ▶ Combustible solid which burns but propagates flame with difficulty; it is estimated that most organic dusts are combustible (circa 70%) - according to the circumstances under which the combustion process occurs, such materials may cause fires and / or dust explosions. ▶ Organic powders when finely divided over a range of concentrations regardless of particulate size or shape and suspended in air or some other oxidizing medium may form explosive dust-air mixtures and result in a fire or dust explosion (including secondary explosions). ▶ Avoid generating dust, particularly clouds of dust in a confined or unventilated space as dusts may form an explosive mixture with air, and any source of ignition, i.e. flame or spark, will cause fire or explosion. Dust clouds generated by the fine grinding of the solid are a particular hazard; accumulations of fine dust (420 micron or less) may burn rapidly and fiercely if ignited - particles exceeding this limit will generally not form flammable dust clouds; once initiated, however, larger particles up to 1400 microns diameter will contribute to the propagation of an explosion. ▶ In the same way as gases and vapours, dusts in the form of a cloud are only ignitable over a range of concentrations; in principle, the concepts of lower explosive limit (LEL) and upper explosive limit (UEL) are applicable to dust clouds but only the LEL is of practical use; - this is because of the inherent difficulty of achieving homogeneous dust clouds at high temperatures (for dusts the LEL is often called the |

- "Minimum Explosible Concentration", MEC).
- ▶ When processed with flammable liquids/vapors/mists, ignitable (hybrid) mixtures may be formed with combustible dusts. Ignitable mixtures will increase the rate of explosion pressure rise and the Minimum Ignition Energy (the minimum amount of energy required to ignite dust clouds - MIE) will be lower than the pure dust in air mixture. The Lower Explosive Limit (LEL) of the vapour/dust mixture will be lower than the individual LELs for the vapors/mists or dusts.
 - ▶ A dust explosion may release of large quantities of gaseous products; this in turn creates a subsequent pressure rise of explosive force capable of damaging plant and buildings and injuring people.
 - ▶ Usually the initial or primary explosion takes place in a confined space such as plant or machinery, and can be of sufficient force to damage or rupture the plant. If the shock wave from the primary explosion enters the surrounding area, it will disturb any settled dust layers, forming a second dust cloud, and often initiate a much larger secondary explosion. All large scale explosions have resulted from chain reactions of this type.
 - ▶ Dry dust can be charged electrostatically by turbulence, pneumatic transport, pouring, in exhaust ducts and during transport.
 - ▶ Build-up of electrostatic charge may be prevented by bonding and grounding.
 - ▶ Powder handling equipment such as dust collectors, dryers and mills may require additional protection measures such as explosion venting.
 - ▶ All movable parts coming in contact with this material should have a speed of less than 1-meter/sec.
 - ▶ A sudden release of statically charged materials from storage or process equipment, particularly at elevated temperatures and/ or pressure, may result in ignition especially in the absence of an apparent ignition source.
 - ▶ One important effect of the particulate nature of powders is that the surface area and surface structure (and often moisture content) can vary widely from sample to sample, depending of how the powder was manufactured and handled; this means that it is virtually impossible to use flammability data published in the literature for dusts (in contrast to that published for gases and vapours).
 - ▶ Autoignition temperatures are often quoted for dust clouds (minimum ignition temperature (MIT)) and dust layers (layer ignition temperature (LIT)); LIT generally falls as the thickness of the layer increases.
- Combustion products include:
carbon monoxide (CO)
carbon dioxide (CO₂)
other pyrolysis products typical of burning organic material.

Dust Explosion Hazard Class 3

Dusts fall into one of three Kst* classes. Class 1 dusts; Kst 1-200 m3/sec; Class 2 dusts; 201-299 m3/sec. Class 3 dusts; Kst 300 or more. Most agricultural dusts (grains, flour etc.) are Class 1; pharmaceuticals and other speciality chemicals are typically Class 1 or 2; most unoxidised metallic dusts are Class 3. The higher the Kst, the more energetically the dust will burn and the greater is the explosion risk and the greater is the speed of the explosion..
Standard test conditions, used to derive the Kst, are representative of industrial conditions, but do not represent an absolute worst case. Increased levels of turbulence increase the speed of the explosion dramatically.

* Kst - a normalised expression of the burning dust pressure rise rate over time.

SECTION 6 Accidental release measures

Personal precautions, protective equipment and emergency procedures

See section 8

Environmental precautions

See section 12

Methods and material for containment and cleaning up

| | |
|---------------------|--|
| Minor Spills | <ul style="list-style-type: none"> ▶ Remove all ignition sources. ▶ Clean up all spills immediately. ▶ Avoid contact with skin and eyes. ▶ Control personal contact with the substance, by using protective equipment. ▶ Use dry clean up procedures and avoid generating dust. ▶ Place in a suitable, labelled container for waste disposal. <p>Environmental hazard - contain spillage.</p> |
| Major Spills | <p>Environmental hazard - contain spillage. Moderate hazard.</p> <ul style="list-style-type: none"> ▶ CAUTION: Advise personnel in area. ▶ Alert Emergency Services and tell them location and nature of hazard. ▶ Control personal contact by wearing protective clothing. ▶ Prevent, by any means available, spillage from entering drains or water courses. ▶ Recover product wherever possible. ▶ IF DRY: Use dry clean up procedures and avoid generating dust. Collect residues and place in sealed plastic bags or other containers for disposal. IF WET: Vacuum/shovel up and place in labelled containers for disposal. ▶ ALWAYS: Wash area down with large amounts of water and prevent runoff into drains. ▶ If contamination of drains or waterways occurs, advise Emergency Services. |

Personal Protective Equipment advice is contained in Section 8 of the SDS.

SECTION 7 Handling and storage

Precautions for safe handling

| | |
|----------------------|---|
| Safe handling | <ul style="list-style-type: none"> ▶ Avoid all personal contact, including inhalation. ▶ Wear protective clothing when risk of exposure occurs. ▶ Use in a well-ventilated area. ▶ Prevent concentration in hollows and sumps. ▶ DO NOT enter confined spaces until atmosphere has been checked. ▶ DO NOT allow material to contact humans, exposed food or food utensils. ▶ Avoid contact with incompatible materials. ▶ When handling, DO NOT eat, drink or smoke. ▶ Keep containers securely sealed when not in use. ▶ Avoid physical damage to containers. ▶ Always wash hands with soap and water after handling. ▶ Work clothes should be laundered separately. Launder contaminated clothing before re-use. |
|----------------------|---|

| | |
|---------------------------------|---|
| | <ul style="list-style-type: none"> ▶ Use good occupational work practice. ▶ Observe manufacturer's storage and handling recommendations contained within this SDS. ▶ Atmosphere should be regularly checked against established exposure standards to ensure safe working conditions are maintained. ▶ Organic powders when finely divided over a range of concentrations regardless of particulate size or shape and suspended in air or some other oxidizing medium may form explosive dust-air mixtures and result in a fire or dust explosion (including secondary explosions) ▶ Minimise airborne dust and eliminate all ignition sources. Keep away from heat, hot surfaces, sparks, and flame. ▶ Establish good housekeeping practices. ▶ Remove dust accumulations on a regular basis by vacuuming or gentle sweeping to avoid creating dust clouds. ▶ Use continuous suction at points of dust generation to capture and minimise the accumulation of dusts. Particular attention should be given to overhead and hidden horizontal surfaces to minimise the probability of a "secondary" explosion. According to NFPA Standard 654, dust layers 1/32 in.(0.8 mm) thick can be sufficient to warrant immediate cleaning of the area. ▶ Do not use air hoses for cleaning. ▶ Minimise dry sweeping to avoid generation of dust clouds. Vacuum dust-accumulating surfaces and remove to a chemical disposal area. Vacuums with explosion-proof motors should be used. ▶ Control sources of static electricity. Dusts or their packages may accumulate static charges, and static discharge can be a source of ignition. ▶ Solids handling systems must be designed in accordance with applicable standards (e.g. NFPA including 654 and 77) and other national guidance. ▶ Do not empty directly into flammable solvents or in the presence of flammable vapors. ▶ The operator, the packaging container and all equipment must be grounded with electrical bonding and grounding systems. Plastic bags and plastics cannot be grounded, and antistatic bags do not completely protect against development of static charges. <p>Empty containers may contain residual dust which has the potential to accumulate following settling. Such dusts may explode in the presence of an appropriate ignition source.</p> <ul style="list-style-type: none"> ▶ Do NOT cut, drill, grind or weld such containers. ▶ In addition ensure such activity is not performed near full, partially empty or empty containers without appropriate workplace safety authorisation or permit. |
| <p>Other information</p> | <ul style="list-style-type: none"> ▶ Store in original containers. ▶ Keep containers securely sealed. ▶ Store in a cool, dry area protected from environmental extremes. ▶ Store away from incompatible materials and foodstuff containers. ▶ Protect containers against physical damage and check regularly for leaks. ▶ Observe manufacturer's storage and handling recommendations contained within this SDS. <p>For major quantities:</p> <ul style="list-style-type: none"> ▶ Consider storage in banded areas - ensure storage areas are isolated from sources of community water (including stormwater, ground water, lakes and streams). ▶ Ensure that accidental discharge to air or water is the subject of a contingency disaster management plan; this may require consultation with local authorities. |

Conditions for safe storage, including any incompatibilities

| | |
|---------------------------------------|---|
| <p>Suitable container</p> | <ul style="list-style-type: none"> ▶ Glass container is suitable for laboratory quantities ▶ Polyethylene or polypropylene container. ▶ Check all containers are clearly labelled and free from leaks. |
| <p>Storage incompatibility</p> | <ul style="list-style-type: none"> ▶ Avoid reaction with oxidising agents |

SECTION 8 Exposure controls / personal protection

Control parameters

Occupational Exposure Limits (OEL)

INGREDIENT DATA

| Source | Ingredient | Material name | TWA | STEL | Peak | Notes |
|--|-------------|--|---------------------|---------------|---|------------------|
| US OSHA Permissible Exposure Limits (PELs) Table Z-3 | bisphenol A | Inert or Nuisance Dust: Respirable fraction | 5 mg/m3 / 15 mppcf | Not Available | Not Available | Not Available |
| US OSHA Permissible Exposure Limits (PELs) Table Z-3 | bisphenol A | Inert or Nuisance Dust: Total Dust | 15 mg/m3 / 50 mppcf | Not Available | Not Available | Not Available |
| US OSHA Permissible Exposure Limits (PELs) Table Z-1 | bisphenol A | Particulates Not Otherwise Regulated (PNOR)- Respirable fraction | 5 mg/m3 | Not Available | Not Available | Not Available |
| US OSHA Permissible Exposure Limits (PELs) Table Z-1 | bisphenol A | Particulates Not Otherwise Regulated (PNOR)- Total dust | 15 mg/m3 | Not Available | Not Available | Not Available |
| US NIOSH Recommended Exposure Limits (RELs) | bisphenol A | Particulates not otherwise regulated | Not Available | Not Available | Not Available | See Appendix D |
| US OSHA Permissible Exposure Limits (PELs) Table Z-1 | phenol | Phenol | 5 ppm / 19 mg/m3 | Not Available | Not Available | Skin designation |
| US NIOSH Recommended Exposure Limits (RELs) | phenol | Phenol | 5 ppm / 19 mg/m3 | Not Available | 15.6 (15-minute) ppm / 60 (15-minute) mg/m3 | [skin] |
| US ACGIH Threshold Limit Values (TLV) | phenol | Phenol | 5 ppm | Not Available | Not Available | Skin; A4; BEI |

Emergency Limits


| Ingredient | TEEL-1 | TEEL-2 | TEEL-3 |
|-------------|---------------|---------------|---------------|
| bisphenol A | 15 mg/m3 | 110 mg/m3 | 650 mg/m3 |
| phenol | Not Available | Not Available | Not Available |

| Ingredient | Original IDLH | Revised IDLH |
|---------------------------------|---------------|---------------|
| bisphenol A | Not Available | Not Available |
| 2,4'-(1-methylethylidene)phenol | Not Available | Not Available |
| phenol | 250 ppm | Not Available |

Occupational Exposure Banding

| Ingredient | Occupational Exposure Band Rating | Occupational Exposure Band Limit |
|---------------------------------|---|----------------------------------|
| 2,4'-(1-methylethylidene)phenol | E | ≤ 0.01 mg/m ³ |
| Notes: | <i>Occupational exposure banding is a process of assigning chemicals into specific categories or bands based on a chemical's potency and the adverse health outcomes associated with exposure. The output of this process is an occupational exposure band (OEB), which corresponds to a range of exposure concentrations that are expected to protect worker health.</i> | |

Exposure controls

| Appropriate engineering controls | <p>Assess operations based upon available dust explosion information to determine the suitability of preventative or protective systems as precautionary measures against possible dust explosions. If prevention is not possible, consider protection by use of containment, venting or suppression of dust handling equipment. Where explosion venting is considered to be the most appropriate method of protection, vent areas should preferably be calculated based on Kst rather than an St value. If nitrogen purging is considered as the protective system, it must operate with an oxygen level below the limiting oxygen concentration. The system should include an oxygen monitoring and shut-down facility in the event of excessive oxygen being detected.</p> <p>The maximum surface temperature of enclosures potentially exposed to this material should be based on values obtained by taking 2/3 of the minimum ignition temperature (MIE) of the dust cloud. The effect of dust layers should be reviewed.</p> <p>An isolated (insulated) human body can readily produce electrostatic discharges in excess of 50 mJ, but have been recorded up to 100 mJ. Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls can be highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection. The basic types of engineering controls are: Process controls which involve changing the way a job activity or process is done to reduce the risk. Enclosure and/or isolation of emission source which keeps a selected hazard "physically" away from the worker and ventilation that strategically "adds" and "removes" air in the work environment. Ventilation can remove or dilute an air contaminant if designed properly. The design of a ventilation system must match the particular process and chemical or contaminant in use. Employers may need to use multiple types of controls to prevent employee overexposure.</p> <ul style="list-style-type: none"> ▶ Local exhaust ventilation is required where solids are handled as powders or crystals; even when particulates are relatively large, a certain proportion will be powdered by mutual friction. ▶ Exhaust ventilation should be designed to prevent accumulation and recirculation of particulates in the workplace. ▶ If in spite of local exhaust an adverse concentration of the substance in air could occur, respiratory protection should be considered. Such protection might consist of: <ul style="list-style-type: none"> (a): particle dust respirators, if necessary, combined with an absorption cartridge; (b): filter respirators with absorption cartridge or canister of the right type; (c): fresh-air hoods or masks <ul style="list-style-type: none"> ▶ Build-up of electrostatic charge on the dust particle, may be prevented by bonding and grounding. ▶ Powder handling equipment such as dust collectors, dryers and mills may require additional protection measures such as explosion venting. <p>Air contaminants generated in the workplace possess varying "escape" velocities which, in turn, determine the "capture velocities" of fresh circulating air required to efficiently remove the contaminant.</p> <table border="1" style="width: 100%;"> <thead> <tr> <th>Type of Contaminant:</th> <th>Air Speed:</th> </tr> </thead> <tbody> <tr> <td>direct spray, spray painting in shallow booths, drum filling, conveyer loading, crusher dusts, gas discharge (active generation into zone of rapid air motion)</td> <td>1-2.5 m/s (200-500 f/min.)</td> </tr> <tr> <td>grinding, abrasive blasting, tumbling, high speed wheel generated dusts (released at high initial velocity into zone of very high rapid air motion).</td> <td>2.5-10 m/s (500-2000 f/min.)</td> </tr> </tbody> </table> <p>Within each range the appropriate value depends on:</p> <table border="1" style="width: 100%;"> <thead> <tr> <th>Lower end of the range</th> <th>Upper end of the range</th> </tr> </thead> <tbody> <tr> <td>1: Room air currents minimal or favourable to capture</td> <td>1: Disturbing room air currents</td> </tr> <tr> <td>2: Contaminants of low toxicity or of nuisance value only</td> <td>2: Contaminants of high toxicity</td> </tr> <tr> <td>3: Intermittent, low production.</td> <td>3: High production, heavy use</td> </tr> <tr> <td>4: Large hood or large air mass in motion</td> <td>4: Small hood-local control only</td> </tr> </tbody> </table> <p>Simple theory shows that air velocity falls rapidly with distance away from the opening of a simple extraction pipe. Velocity generally decreases with the square of distance from the extraction point (in simple cases). Therefore the air speed at the extraction point should be adjusted, accordingly, after reference to distance from the contaminating source. The air velocity at the extraction fan, for example, should be a minimum of 4-10 m/s (800-2000 f/min) for extraction of crusher dusts generated 2 metres distant from the extraction point. Other mechanical considerations, producing performance deficits within the extraction apparatus, make it essential that theoretical air velocities are multiplied by factors of 10 or more when extraction systems are installed or used.</p> | Type of Contaminant: | Air Speed: | direct spray, spray painting in shallow booths, drum filling, conveyer loading, crusher dusts, gas discharge (active generation into zone of rapid air motion) | 1-2.5 m/s (200-500 f/min.) | grinding, abrasive blasting, tumbling, high speed wheel generated dusts (released at high initial velocity into zone of very high rapid air motion). | 2.5-10 m/s (500-2000 f/min.) | Lower end of the range | Upper end of the range | 1: Room air currents minimal or favourable to capture | 1: Disturbing room air currents | 2: Contaminants of low toxicity or of nuisance value only | 2: Contaminants of high toxicity | 3: Intermittent, low production. | 3: High production, heavy use | 4: Large hood or large air mass in motion | 4: Small hood-local control only |
|--|--|----------------------|------------|--|----------------------------|--|------------------------------|------------------------|------------------------|---|---------------------------------|---|----------------------------------|----------------------------------|-------------------------------|---|----------------------------------|
| | Type of Contaminant: | Air Speed: | | | | | | | | | | | | | | | |
| direct spray, spray painting in shallow booths, drum filling, conveyer loading, crusher dusts, gas discharge (active generation into zone of rapid air motion) | 1-2.5 m/s (200-500 f/min.) | | | | | | | | | | | | | | | | |
| grinding, abrasive blasting, tumbling, high speed wheel generated dusts (released at high initial velocity into zone of very high rapid air motion). | 2.5-10 m/s (500-2000 f/min.) | | | | | | | | | | | | | | | | |
| Lower end of the range | Upper end of the range | | | | | | | | | | | | | | | | |
| 1: Room air currents minimal or favourable to capture | 1: Disturbing room air currents | | | | | | | | | | | | | | | | |
| 2: Contaminants of low toxicity or of nuisance value only | 2: Contaminants of high toxicity | | | | | | | | | | | | | | | | |
| 3: Intermittent, low production. | 3: High production, heavy use | | | | | | | | | | | | | | | | |
| 4: Large hood or large air mass in motion | 4: Small hood-local control only | | | | | | | | | | | | | | | | |
| Personal protection |  | | | | | | | | | | | | | | | | |
| Eye and face protection | <ul style="list-style-type: none"> ▶ Safety glasses with side shields. ▶ Chemical goggles. ▶ Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lenses or restrictions on use, should be created for each workplace or task. This should include a review of lens absorption and adsorption for the class of chemicals in use and an account of injury experience. Medical and first-aid personnel should be trained in their removal and suitable equipment should be readily available. In the event of chemical exposure, begin eye irrigation immediately and remove contact lens as soon as practicable. Lens should be removed at the first signs of eye redness or irritation - lens should be removed in a clean environment only after workers have washed hands thoroughly. [CDC NIOSH Current Intelligence Bulletin 59], [AS/NZS 1336 or national equivalent] | | | | | | | | | | | | | | | | |
| Skin protection | See Hand protection below | | | | | | | | | | | | | | | | |
| Hands/feet protection | <p>NOTE:</p> <ul style="list-style-type: none"> ▶ The material may produce skin sensitisation in predisposed individuals. Care must be taken, when removing gloves and other protective equipment, to avoid all possible skin contact. ▶ Contaminated leather items, such as shoes, belts and watch-bands should be removed and destroyed. <p>The selection of suitable gloves does not only depend on the material, but also on further marks of quality which vary from manufacturer to manufacturer. Where the chemical is a preparation of several substances, the resistance of the glove material can not be calculated in advance</p> | | | | | | | | | | | | | | | | |

and has therefore to be checked prior to the application.
The exact break through time for substances has to be obtained from the manufacturer of the protective gloves and has to be observed when making a final choice.
Personal hygiene is a key element of effective hand care. Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-perfumed moisturiser is recommended.
Suitability and durability of glove type is dependent on usage. Important factors in the selection of gloves include:

- frequency and duration of contact,
- chemical resistance of glove material,
- glove thickness and
- dexterity

Select gloves tested to a relevant standard (e.g. Europe EN 374, US F739, AS/NZS 2161.1 or national equivalent).

- When prolonged or frequently repeated contact may occur, a glove with a protection class of 5 or higher (breakthrough time greater than 240 minutes according to EN 374, AS/NZS 2161.10.1 or national equivalent) is recommended.
- When only brief contact is expected, a glove with a protection class of 3 or higher (breakthrough time greater than 60 minutes according to EN 374, AS/NZS 2161.10.1 or national equivalent) is recommended.
- Some glove polymer types are less affected by movement and this should be taken into account when considering gloves for long-term use.
- Contaminated gloves should be replaced.

As defined in ASTM F-739-96 in any application, gloves are rated as:

- Excellent when breakthrough time > 480 min
- Good when breakthrough time > 20 min
- Fair when breakthrough time < 20 min
- Poor when glove material degrades

For general applications, gloves with a thickness typically greater than 0.35 mm, are recommended.
It should be emphasised that glove thickness is not necessarily a good predictor of glove resistance to a specific chemical, as the permeation efficiency of the glove will be dependent on the exact composition of the glove material. Therefore, glove selection should also be based on consideration of the task requirements and knowledge of breakthrough times.
Glove thickness may also vary depending on the glove manufacturer, the glove type and the glove model. Therefore, the manufacturers' technical data should always be taken into account to ensure selection of the most appropriate glove for the task.
Note: Depending on the activity being conducted, gloves of varying thickness may be required for specific tasks. For example:

- Thinner gloves (down to 0.1 mm or less) may be required where a high degree of manual dexterity is needed. However, these gloves are only likely to give short duration protection and would normally be just for single use applications, then disposed of.
- Thicker gloves (up to 3 mm or more) may be required where there is a mechanical (as well as a chemical) risk i.e. where there is abrasion or puncture potential

Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-perfumed moisturiser is recommended.
Experience indicates that the following polymers are suitable as glove materials for protection against undissolved, dry solids, where abrasive particles are not present.

- polychloroprene.
- nitrile rubber.
- butyl rubber.
- fluorocautchouc.
- polyvinyl chloride.

Gloves should be examined for wear and/ or degradation constantly.

Body protection See Other protection below

Other protection

- Overalls.
- P.V.C apron.
- Barrier cream.
- Skin cleansing cream.
- Eye wash unit.

Recommended material(s)

GLOVE SELECTION INDEX

Glove selection is based on a modified presentation of the: **"Forsberg Clothing Performance Index"**.

The effect(s) of the following substance(s) are taken into account in the **computer-generated** selection:
BISPHENOL A

| Material | CPI |
|-------------------|-----|
| BUTYL | A |
| BUTYL/NEOPRENE | A |
| NATURAL+NEOPRENE | A |
| NEOPRENE | A |
| NEOPRENE/NATURAL | A |
| PE/EVAL/PE | A |
| TEFLON | A |
| VITON | A |
| VITON/NEOPRENE | A |
| NATURAL RUBBER | B |
| NAT+NEOPR+NITRILE | C |
| NITRILE | C |
| PVA | C |
| PVC | C |

* CPI - Chemwatch Performance Index

A: Best Selection

B: Satisfactory; may degrade after 4 hours continuous immersion

C: Poor to Dangerous Choice for other than short term immersion

Respiratory protection

Type A-P Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

| Required Minimum Protection Factor | Half-Face Respirator | Full-Face Respirator | Powered Air Respirator |
|------------------------------------|----------------------|----------------------|------------------------|
| up to 10 x ES | A P1 Air-line* | - | A PAPR-P1 |
| up to 50 x ES | Air-line** | A P2 | A PAPR-P2 |
| up to 100 x ES | - | A P3 | - |
| | | Air-line* | - |
| 100+ x ES | - | Air-line** | A PAPR-P3 |

* - Negative pressure demand ** - Continuous flow

A(All classes) = Organic vapours, B AUS or B1 = Acid gasses, B2 = Acid gas or hydrogen cyanide(HCN), B3 = Acid gas or hydrogen cyanide(HCN), E = Sulfur dioxide(SO2), G = Agricultural chemicals, K = Ammonia(NH3), Hg = Mercury, NO = Oxides of nitrogen, MB = Methyl bromide, AX = Low boiling point organic compounds(below 65 degC)

Respirators may be necessary when engineering and administrative controls do not adequately prevent exposures.

The decision to use respiratory protection should be based on professional judgment that takes into account toxicity information, exposure measurement data, and frequency and likelihood of the worker's exposure - ensure users are not subject to high thermal loads which may result in heat stress or distress due to personal protective equipment (powered, positive flow, full face apparatus may be an option).

Published occupational exposure limits, where they exist, will assist in determining the adequacy of the selected respiratory protection. These may be government mandated or vendor recommended.

Certified respirators will be useful for protecting workers from inhalation of particulates when properly selected and fit tested as part of a complete respiratory protection program.

Continued...

NOTE: As a series of factors will influence the actual performance of the glove, a final selection must be based on detailed observation. -
* Where the glove is to be used on a short term, casual or infrequent basis, factors such as "feel" or convenience (e.g. disposability), may dictate a choice of gloves which might otherwise be unsuitable following long-term or frequent use. A qualified practitioner should be consulted.

- Where protection from nuisance levels of dusts are desired, use type N95 (US) or type P1 (EN143) dust masks. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU)
- Use approved positive flow mask if significant quantities of dust becomes airborne.
- Try to avoid creating dust conditions.

SECTION 9 Physical and chemical properties

Information on basic physical and chemical properties

| | | | |
|---|--|--|----------------|
| Appearance | White to light tan flakes or powder with mild phenolic odour. Insoluble in water. Soluble in alcohol and dilute alkalis. Slightly soluble in carbon tetrachloride. | | |
| Physical state | Divided Solid | Relative density (Water = 1) | 1.20 |
| Odour | Not Available | Partition coefficient n-octanol / water | 2.2-3.2 |
| Odour threshold | Not Available | Auto-ignition temperature (°C) | 570 |
| pH (as supplied) | Not Applicable | Decomposition temperature | Not Available |
| Melting point / freezing point (°C) | 153-156 | Viscosity (cSt) | Not Applicable |
| Initial boiling point and boiling range (°C) | 220 (@ 4 mm) | Molecular weight (g/mol) | 228.31 |
| Flash point (°C) | 213 (OC) | Taste | Not Available |
| Evaporation rate | Not Applicable | Explosive properties | Not Available |
| Flammability | Not Applicable | Oxidising properties | Not Available |
| Upper Explosive Limit (%) | Not Available | Surface Tension (dyn/cm or mN/m) | Not Applicable |
| Lower Explosive Limit (%) | 0.019 g/l | Volatile Component (%vol) | Negligible |
| Vapour pressure (kPa) | Negligible | Gas group | Not Available |
| Solubility in water | Immiscible | pH as a solution (%) | Not Applicable |
| Vapour density (Air = 1) | Not Available | VOC g/L | Not Available |

SECTION 10 Stability and reactivity

| | |
|---|--|
| Reactivity | See section 7 |
| Chemical stability | <ul style="list-style-type: none"> Unstable in the presence of incompatible materials. Product is considered stable. Hazardous polymerisation will not occur. |
| Possibility of hazardous reactions | See section 7 |
| Conditions to avoid | See section 7 |
| Incompatible materials | See section 7 |
| Hazardous decomposition products | See section 5 |

SECTION 11 Toxicological information

Information on toxicological effects

| | |
|---------------------|--|
| Inhaled | <p>At room temperature, exposures to vapours are unlikely due to physical properties, higher temperatures may generate vapour levels sufficient to cause irritation. Dusts may cause sneezing.</p> <p>The material can cause respiratory irritation in some persons. The body's response to such irritation can cause further lung damage. Persons with impaired respiratory function, airway diseases and conditions such as emphysema or chronic bronchitis, may incur further disability if excessive concentrations of particulate are inhaled.</p> <p>If prior damage to the circulatory or nervous systems has occurred or if kidney damage has been sustained, proper screenings should be conducted on individuals who may be exposed to further risk if handling and use of the material result in excessive exposures.</p> <p>Inhalation of vapours or aerosols (mists, fumes), generated by the material during the course of normal handling, may be damaging to the health of the individual.</p> |
| Ingestion | <p>Single dose oral toxicity is low. Ingestion of large amounts may cause injury.</p> <p>Although ingestion is not thought to produce harmful effects (as classified under EC Directives), the material may still be damaging to the health of the individual, following ingestion, especially where pre-existing organ (e.g. liver, kidney) damage is evident.</p> |
| Skin Contact | <p>Brief skin contact is unlikely to cause irritation. Prolonged or repeated exposure may cause some skin irritation, even a burn. May be a weak skin sensitiser. Prolonged skin exposure is not likely to result in absorption of harmful amounts.</p> <p>The material is not thought to be a skin irritant (as classified by EC Directives using animal models). Abrasive damage however, may result from prolonged exposures.</p> <p>Skin contact with the material may damage the health of the individual; systemic effects may result following absorption.</p> <p>Open cuts, abraded or irritated skin should not be exposed to this material</p> <p>Entry into the blood-stream, through, for example, cuts, abrasions or lesions, may produce systemic injury with harmful effects. Examine the skin prior to the use of the material and ensure that any external damage is suitably protected.</p> |
| Eye | If applied to the eyes, this material causes severe eye damage. |

| Chronic | <p>Long-term exposure to respiratory irritants may result in airways disease, involving difficulty breathing and related whole-body problems. Skin contact with the material is more likely to cause a sensitisation reaction in some persons compared to the general population. Ample evidence from experiments exists that there is a suspicion this material directly reduces fertility.</p> <p>There has been some concern that this material can cause cancer or mutations but there is not enough data to make an assessment. Substance accumulation, in the human body, may occur and may cause some concern following repeated or long-term occupational exposure. Bisphenol A may have effects similar to female sex hormones and when administered to pregnant women, may damage the foetus. It may also damage male reproductive organs and sperm.</p> | | | | | | | | | | | | | | | |
|---|--|----------|------------|--|----------------------------------|---|--|--|-----------------------------------|--|------------------------------------|--|---|--|--|--|
| bisphenol A | <table border="1"> <thead> <tr> <th>TOXICITY</th> <th>IRRITATION</th> </tr> </thead> <tbody> <tr> <td>Dermal (rabbit) LD50: ~3000 mg/kg^[1]</td> <td>Eye (rabbit): 0.25 mg/24h-SEVERE</td> </tr> <tr> <td>Oral(Rat) LD50; 1200 mg/kg^[2]</td> <td>Eye: adverse effect observed (irritating)^[1]</td> </tr> <tr> <td></td> <td>Skin (rabbit): 250 mg open - mild</td> </tr> <tr> <td></td> <td>Skin (rabbit): 500 mg/24h - mild</td> </tr> <tr> <td></td> <td>Skin: adverse effect observed (irritating)^[1]</td> </tr> <tr> <td></td> <td>Skin: no adverse effect observed (not irritating)^[1]</td> </tr> </tbody> </table> | TOXICITY | IRRITATION | Dermal (rabbit) LD50: ~3000 mg/kg ^[1] | Eye (rabbit): 0.25 mg/24h-SEVERE | Oral(Rat) LD50; 1200 mg/kg ^[2] | Eye: adverse effect observed (irritating) ^[1] | | Skin (rabbit): 250 mg open - mild | | Skin (rabbit): 500 mg/24h - mild | | Skin: adverse effect observed (irritating) ^[1] | | Skin: no adverse effect observed (not irritating) ^[1] | |
| TOXICITY | IRRITATION | | | | | | | | | | | | | | | |
| Dermal (rabbit) LD50: ~3000 mg/kg ^[1] | Eye (rabbit): 0.25 mg/24h-SEVERE | | | | | | | | | | | | | | | |
| Oral(Rat) LD50; 1200 mg/kg ^[2] | Eye: adverse effect observed (irritating) ^[1] | | | | | | | | | | | | | | | |
| | Skin (rabbit): 250 mg open - mild | | | | | | | | | | | | | | | |
| | Skin (rabbit): 500 mg/24h - mild | | | | | | | | | | | | | | | |
| | Skin: adverse effect observed (irritating) ^[1] | | | | | | | | | | | | | | | |
| | Skin: no adverse effect observed (not irritating) ^[1] | | | | | | | | | | | | | | | |
| 2,4'-(1-methylethylidene)phenol | <table border="1"> <thead> <tr> <th>TOXICITY</th> <th>IRRITATION</th> </tr> </thead> <tbody> <tr> <td>Not Available</td> <td>Not Available</td> </tr> </tbody> </table> | TOXICITY | IRRITATION | Not Available | Not Available | | | | | | | | | | | |
| TOXICITY | IRRITATION | | | | | | | | | | | | | | | |
| Not Available | Not Available | | | | | | | | | | | | | | | |
| phenol | <table border="1"> <thead> <tr> <th>TOXICITY</th> <th>IRRITATION</th> </tr> </thead> <tbody> <tr> <td>dermal (rat) LD50: 525 mg/kg^[1]</td> <td>Eye(rabbit): 100 mg rinse - mild</td> </tr> <tr> <td>Inhalation(Mouse) LC50; 0.177 mg/L4h^[2]</td> <td>Eye(rabbit): 5 mg - SEVERE</td> </tr> <tr> <td>Oral(Mouse) LD50; 270 mg/kg^[2]</td> <td>Skin(rabbit): 500 mg open -SEVERE</td> </tr> <tr> <td></td> <td>Skin(rabbit): 500 mg/24hr - SEVERE</td> </tr> </tbody> </table> | TOXICITY | IRRITATION | dermal (rat) LD50: 525 mg/kg ^[1] | Eye(rabbit): 100 mg rinse - mild | Inhalation(Mouse) LC50; 0.177 mg/L4h ^[2] | Eye(rabbit): 5 mg - SEVERE | Oral(Mouse) LD50; 270 mg/kg ^[2] | Skin(rabbit): 500 mg open -SEVERE | | Skin(rabbit): 500 mg/24hr - SEVERE | | | | | |
| TOXICITY | IRRITATION | | | | | | | | | | | | | | | |
| dermal (rat) LD50: 525 mg/kg ^[1] | Eye(rabbit): 100 mg rinse - mild | | | | | | | | | | | | | | | |
| Inhalation(Mouse) LC50; 0.177 mg/L4h ^[2] | Eye(rabbit): 5 mg - SEVERE | | | | | | | | | | | | | | | |
| Oral(Mouse) LD50; 270 mg/kg ^[2] | Skin(rabbit): 500 mg open -SEVERE | | | | | | | | | | | | | | | |
| | Skin(rabbit): 500 mg/24hr - SEVERE | | | | | | | | | | | | | | | |
| Legend: | <p>1. Value obtained from Europe ECHA Registered Substances - Acute toxicity 2.* Value obtained from manufacturer's SDS. Unless otherwise specified data extracted from RTECS - Register of Toxic Effect of chemical Substances</p> | | | | | | | | | | | | | | | |

| | |
|--------------------|---|
| BISPHENOL A | <p>For bisphenol A (BPA)</p> <p>Following oral administration absorption of BPA is rapid and extensive while dermal absorption is limited. Extensive first pass metabolism occurs following absorption from the gastrointestinal tract with glucuronide conjugation being the major metabolic pathway. Bisphenol A is of low acute toxicity (rodent oral LD50 values from 3300-4100 mg/kg, a rabbit oral LD50 value 2230 mg/kg and a rat acute inhalation 6-hour LC50 value >170 mg/m³). Bisphenol A is not a skin irritant, however, it is severely irritating to the eyes. BPA was negative in gene mutation and clastogenicity assays in cultured mammalian cells, as well as in a micronucleus test for clastogenicity <i>in vivo</i>; therefore, BPA is considered not to present a genotoxic concern for human health. BPA results in minimal effects on the liver and kidney (LOAEL from chronic exposure in the diet was 50 mg/kg/day). For reproductive toxicity, data from a three-generation study in the rat, BPA was not a selective reproductive toxicant at doses ranging from 0.001 to 500 mg/kg/day. BPA is not a developmental toxicant in rats or mice.</p> <p>Inconsistent findings are reported in the "low dose" literature for bisphenol A. The inherent challenge of conducting these types of studies may be exacerbated with bisphenol A because the endpoints of concern are endocrine-mediated and potentially impacted by factors that include phytoestrogen content of the animal feed, extent of bisphenol A exposure from caging or water bottles, and the alleged sensitivity of the animal model to oestrogens.</p> <p>High-dose studies are less susceptible to these types of influences because the toxicologic response should be more robust and less variable. Several large, robust, well designed studies with multiple dose groups using several strains of rats and mice have been conducted and none of these detected any adverse reproductive effects at low to moderate dosage levels of BPA administered via the relevant route of human exposures. Further, none of these studies detected changes in prostate weight, age at puberty (rat), pathology or tumors in any tissue, or reproductive tract malformations.</p> <p>Every chemical that produces low dose cellular and molecular alterations of endocrine function also produces a cascade of effects increasing in severity resulting in clearly adverse alterations at higher doses, albeit the effects can be different from those seen at low doses. With these endocrine disrupters, but not BPA, the low dose effects are often causally linked to the high-dose adverse effects of the chemical. This is true for androgens like testosterone and trenbolone, estrogens like DES, 17beta-oestradiol and ethinyl oestradiol, xenoestrogens like methoxychlor and genistein, and antiandrogens like vinclozolin, for example. Hence, the failure of BPA to produce reproducible adverse effects via a relevant route of exposure, coupled with the lack of robustness of the many of the low dose studies (sample size, dose range, statistical analyses and experimental design, GLP) and the inability to reproduce many of these effects of any adverse effect strains the credibility of some of these study results.</p> <p>The lack of reproducibility of the low dose effects, the absence of toxicity in those low-dose-affected tissues at high-doses, and the uncertain adversity of the reported effects lead to the conclusion that there is "minimal" concern for reproductive effects.</p> <p>In contrast, the literature on bisphenol A effects on neural and behavioral response is more consistent with respect to the number of "positive" studies although it should be noted that the high-dose studies that proved to be the most useful for evaluating reproductive effects did not adequately assess neural and behavioral responses. In addition, even though different investigators assessed different neural and behavioral endpoints, an expert Panel concluded that the overall findings suggest that bisphenol A may be associated with neural changes in the brain and behavioral alterations related to sexual dimorphism in rodents. For this reason, the Panel expressed "some" concern for these effects even though it is not clear the reported effects constitute an adverse toxicological response. In summary:</p> <p>For pregnant women and fetuses, the Expert Panel has different levels of concern for the different developmental endpoints that may be susceptible to bisphenol A disruption, as follows:</p> <ul style="list-style-type: none"> ▸ For neural and behavioral effects, the Expert Panel has some concern; ▸ For prostate effects, the Expert Panel has minimal concern; ▸ For the potential effect of accelerated puberty, the Expert Panel has minimal concern; and ▸ For birth defects and malformations, the Expert Panel has negligible concern. <p>For infants and children, the Expert Panel has the following levels of concern for biological processes that might be altered by Bisphenol A, as follows:</p> <ul style="list-style-type: none"> ▸ Some concern for neural and behavioral effects; and ▸ Minimal concern for the effect of accelerated puberty. <p>For adults, the Expert Panel has negligible concern for adverse reproductive effects following exposures in the general population to Bisphenol A. For highly exposed subgroups, such as occupationally exposed populations, the level of concern is elevated to minimal.</p> <p>NTP-CERHR Monograph on the Potential Human Reproductive and Developmental Effects of Bisphenol A National Toxicology Program US Department of Health and Human Services September 2008 NTP Publication No 08-5994</p> <p>The material may cause skin irritation after prolonged or repeated exposure and may produce on contact skin redness, swelling, the production of vesicles, scaling and thickening of the skin.</p> |
|--------------------|---|

| | | | |
|--|---|--|----------|
| <p>2,4'-(1-METHYLETHYLIDENE)PHENOL</p> | <p>No significant acute toxicological data identified in literature search. The substance is a component of BPA tars (CAS RN: 72162-28-8; syn. 2-propanone, reaction products with phenol) residual mixture resulting from the production of bisphenol A (p,p-BPA; CAS RN 80-05-7). Based on the chemical nature of BPA Tars the data for BPA is considered to define the toxicity of BPA Tars. The components of BPA tars are primarily larger dimers/ trimers of BPA and would be expected to be less water soluble. CComponents, of higher molecular weight, are expected to be less bioavailable and less chemically and biologically reactive. Further evidence that the bisphenolic components of BPA Tars would yield similar or lesser results in toxicology studies comes from acute toxicity studies and an Ames test done on one of the bisphenolic impurities, spirobiindane (CAS No. 1568-80-5). The acute oral and dermal LD50 values for spirobiindane were >5000 mg/kg and >2000 mg/kg, respectively. Spirobiindane was also negative in the Salmonella Reverse Mutation assay. Acute toxicity: Following oral administration absorption of BPA is rapid and extensive while dermal absorption is limited. Extensive first pass metabolism occurs following absorption from the gastrointestinal tract with glucuronide conjugation being the major metabolic pathway. Bisphenol A is of low acute toxicity (rodent oral LD50 values from 3300-4100 mg/kg, a rabbit oral LD50 value 2230 mg/kg and a rat acute inhalation 6-hour LC50 value >170 mg/m3). Bisphenol A is not a skin irritant, however, it is severely irritating to the eyes. Repeat dose toxicity: BPA results in minimal effects on the liver and kidney (LOAEL from chronic exposure in the diet was 50 mg/kg/day). Genotoxicity: BPA was negative in gene mutation and clastogenicity assays in cultured mammalian cells, as well as in a micronucleus test for clastogenicity <i>in vivo</i>; therefore, BPA is considered not to present a genotoxic concern for human health. The higher molecular weight components of BPA Tars are not anticipated to be mutagenic. Reproductive and developmental toxicity: For reproductive toxicity, data from a three-generation study in the rat, BPA was not a selective reproductive toxicant at doses ranging from 0.001 to 500 mg/kg/day. BPA is not a developmental toxicant in rats or mice.</p> | | |
| <p>PHENOL</p> | <p>The material may produce severe irritation to the eye causing pronounced inflammation. Repeated or prolonged exposure to irritants may produce conjunctivitis. The material may cause severe skin irritation after prolonged or repeated exposure and may produce on contact skin redness, swelling, the production of vesicles, scaling and thickening of the skin. Repeated exposures may produce severe ulceration. The substance is classified by IARC as Group 3: NOT classifiable as to its carcinogenicity to humans. Evidence of carcinogenicity may be inadequate or limited in animal testing.</p> | | |
| <p>BISPHENOL A & 2,4'-(1-METHYLETHYLIDENE)PHENOL</p> | <p>The following information refers to contact allergens as a group and may not be specific to this product. Contact allergies quickly manifest themselves as contact eczema, more rarely as urticaria or Quincke's oedema. The pathogenesis of contact eczema involves a cell-mediated (T lymphocytes) immune reaction of the delayed type. Other allergic skin reactions, e.g. contact urticaria, involve antibody-mediated immune reactions. The significance of the contact allergen is not simply determined by its sensitisation potential: the distribution of the substance and the opportunities for contact with it are equally important. A weakly sensitising substance which is widely distributed can be a more important allergen than one with stronger sensitising potential with which few individuals come into contact. From a clinical point of view, substances are noteworthy if they produce an allergic test reaction in more than 1% of the persons tested. The chemical structure of hydroxylated diphenylalkanes or bisphenols consists of two phenolic rings joined together through a bridging carbon. This class of endocrine disruptors that mimic oestrogens is widely used in industry, particularly in plastics. Bisphenol A (BPA) and some related compounds exhibit oestrogenic activity in human breast cancer cell line MCF-7, but there were remarkable differences in activity. Several derivatives of BPA exhibited significant thyroid hormonal activity towards rat pituitary cell line GH3, which releases growth hormone in a thyroid hormone-dependent manner. However, BPA and several other derivatives did not show such activity. Results suggest that the 4-hydroxyl group of the A-phenyl ring and the B-phenyl ring of BPA derivatives are required for these hormonal activities, and substituents at the 3,5-positions of the phenyl rings and the bridging alkyl moiety markedly influence the activities. Bisphenols promoted cell proliferation and increased the synthesis and secretion of cell type-specific proteins. When ranked by proliferative potency, the longer the alkyl substituent at the bridging carbon, the lower the concentration needed for maximal cell yield; the most active compound contained two propyl chains at the bridging carbon. Bisphenols with two hydroxyl groups in the para position and an angular configuration are suitable for appropriate hydrogen bonding to the acceptor site of the oestrogen receptor. In vitro cell models were used to evaluate the ability of 22 bisphenols (BPs) to induce or inhibit estrogenic and androgenic activity. BPA, Bisphenol AF (BPAF), bisphenol Z (BPZ), bisphenol C (BPC), tetramethyl bisphenol A (TMBPA), bisphenol S (BPS), bisphenol E (BPE), 4,4-bisphenol F (4,4-BPF), bisphenol AP (BPAP), bisphenol B (BPB), tetrachlorobisphenol A (TCBPA), and benzylparaben (PHBB) induced estrogen receptor (ER)alpha and/or ERbeta-mediated activity. With the exception of BPS, TCBPA, and PHBB, these same BPs were also androgen receptor (AR) antagonists. Only 3 BPs were found to be ER antagonists. Bisphenol P (BPP) selectively inhibited ERbeta-mediated activity and 4-(4-phenylmethoxyphenyl)sulfonylphenol (BPS-MPE) and 2,4-bisphenol S (2,4-BPS) selectively inhibited ERalpha-mediated activity. None of the BPs induced AR-mediated activity.</p> | | |
| <p>BISPHENOL A & 2,4'-(1-METHYLETHYLIDENE)PHENOL & PHENOL</p> | <p>Asthma-like symptoms may continue for months or even years after exposure to the material ends. This may be due to a non-allergic condition known as reactive airways dysfunction syndrome (RADS) which can occur after exposure to high levels of highly irritating compound. Main criteria for diagnosing RADS include the absence of previous airways disease in a non-atopic individual, with sudden onset of persistent asthma-like symptoms within minutes to hours of a documented exposure to the irritant. Other criteria for diagnosis of RADS include a reversible airflow pattern on lung function tests, moderate to severe bronchial hyperreactivity on methacholine challenge testing, and the lack of minimal lymphocytic inflammation, without eosinophilia. RADS (or asthma) following an irritating inhalation is an infrequent disorder with rates related to the concentration of and duration of exposure to the irritating substance. On the other hand, industrial bronchitis is a disorder that occurs as a result of exposure due to high concentrations of irritating substance (often particles) and is completely reversible after exposure ceases. The disorder is characterized by difficulty breathing, cough and mucus production.</p> | | |
| <p>Acute Toxicity</p> | <p>✗</p> | <p>Carcinogenicity</p> | <p>✗</p> |
| <p>Skin Irritation/Corrosion</p> | <p>✗</p> | <p>Reproductivity</p> | <p>✓</p> |
| <p>Serious Eye Damage/Irritation</p> | <p>✓</p> | <p>STOT - Single Exposure</p> | <p>✓</p> |
| <p>Respiratory or Skin sensitisation</p> | <p>✓</p> | <p>STOT - Repeated Exposure</p> | <p>✗</p> |
| <p>Mutagenicity</p> | <p>✗</p> | <p>Aspiration Hazard</p> | <p>✗</p> |

Legend: ✗ – Data either not available or does not fill the criteria for classification
✓ – Data available to make classification

SECTION 12 Ecological information

Toxicity

| bisphenol A | Endpoint | Test Duration (hr) | Species | Value | Source |
|-------------|-----------|--------------------|-------------------------------|---------------|--------|
| | ErC50 | 72h | Algae or other aquatic plants | 2.7-3.1mg/l | 1 |
| | NOEC(ECx) | 96h | Crustacea | 0.51mg/l | 1 |
| | BCF | 1008h | Fish | 5.1-13.3 | 7 |
| | EC50 | 72h | Algae or other aquatic plants | 1.25-1.89mg/l | 4 |
| | LC50 | 96h | Fish | 3-5mg/l | 2 |

Continued...

| | | | | | |
|--|--|---------------------------|-------------------------------|-------------------|---------------|
| | EC50 | 48h | Crustacea | 10.2mg/l | 1 |
| | EC50 | 96h | Algae or other aquatic plants | 1mg/l | 1 |
| 2,4'-(1-methylethylidene)phenol | Endpoint | Test Duration (hr) | Species | Value | Source |
| | Not Available | Not Available | Not Available | Not Available | Not Available |
| phenol | Endpoint | Test Duration (hr) | Species | Value | Source |
| | EC50 | 72h | Algae or other aquatic plants | 48.937-57.407mg/L | 4 |
| | LC50 | 96h | Fish | 2.809-5.554mg/L | 4 |
| | EC50 | 48h | Crustacea | 3.1mg/l | 1 |
| | EC10(ECx) | 504h | Crustacea | 0.05mg/l | 2 |
| | EC50 | 96h | Algae or other aquatic plants | 10.6mg/L | 4 |
| Legend: | <i>Extracted from 1. IUCLID Toxicity Data 2. Europe ECHA Registered Substances - Ecotoxicological Information - Aquatic Toxicity 3. EPIWIN Suite V3.12 (QSAR) - Aquatic Toxicity Data (Estimated) 4. US EPA, Ecotox database - Aquatic Toxicity Data 5. ECETOC Aquatic Hazard Assessment Data 6. NITE (Japan) - Bioconcentration Data 7. METI (Japan) - Bioconcentration Data 8. Vendor Data</i> | | | | |

Toxic to aquatic organisms.

Do NOT allow product to come in contact with surface waters or to intertidal areas below the mean high water mark. Do not contaminate water when cleaning equipment or disposing of equipment wash-waters.

Wastes resulting from use of the product must be disposed of on site or at approved waste sites.

May cause long-term adverse effects in the aquatic environment.

For bisphenol A and related bisphenols:

Environmental fate:

Biodegradability (28 d) 89% - Easily biodegradable

Bioconcentration factor (BCF) 7.8 mg/l

Bisphenol A, its derivatives and analogues, can be released from polymers, resins and certain substances by metabolic products

Substance does not meet the criteria for PBT or vPvB according to Regulation (EC) No 1907/2006, Annex XIII

As an environmental contaminant, bisphenol A interferes with nitrogen fixation at the roots of leguminous plants associated with the bacterial symbiont *Sinorhizobium meliloti*. Despite a half-life in the soil of only 1-10 days, its ubiquity makes it an important pollutant. According to Environment Canada, "initial assessment shows that at low levels, bisphenol A can harm fish and organisms over time. Studies also indicate that it can currently be found in municipal wastewater." However, a study conducted in the United States found that 91-98% of bisphenol A may be removed from water during treatment at municipal water treatment plants.

Ecotoxicity:

Fish LC50 (96 h): 4.6 mg/l (freshwater fish); 11 mg/l (saltwater fish); NOEC 0.016 mg/l (freshwater fish- 144 d); 0.064 mg/l (saltwater fish 164 d)

Fresh water invertebrates EC50 (48 h): 10.2 mg/l; NOEC 0.025 mg/l - 328 d)

Marine water invertebrate EC50 (96 h): 1.1 mg/l; NOEC 0.17 mg/l (28 d)

Freshwater algae (96 h): 2.73 mg/l

Marine water algae (96 h): 1.1 mg/l

Fresh water plant EC50 (7 d): 20 mg/l; NOEC 7.8 mg/l

In general, studies have shown that bisphenol A can affect growth, reproduction and development in aquatic organisms.

Among freshwater organisms, fish appear to be the most sensitive species. Evidence of endocrine-related effects in fish, aquatic invertebrates, amphibians and reptiles has been reported at environmentally relevant exposure levels lower than those required for acute toxicity. There is a widespread variation in reported values for endocrine-related effects, but many fall in the range of 1 ug/L to 1 mg/L

A 2009 review of the biological impacts of plasticisers on wildlife published by the Royal Society with a focus on annelids (both aquatic and terrestrial), molluscs, crustaceans, insects, fish and amphibians concluded that bisphenol A has been shown to affect reproduction in all studied animal groups, to impair development in crustaceans and amphibians and to induce genetic aberrations.

A large 2010 study of two rivers in Canada found that areas contaminated with hormone-like chemicals including bisphenol A showed females made up 85 per cent of the population of a certain fish, while females made up only 55 per cent in uncontaminated areas.

Although abundant data are available on the toxicity of bisphenol-A (2,2-bis (4-hydroxydiphenyl)propane;(BPA) A variety of BPs were examined for their acute toxicity against *Daphnia magna*, mutagenicity, and oestrogenic activity using the Daphtoxkit (Creasel Ltd.), the umu test system, and the yeast two-hybrid system, respectively, in comparison with BPA. BPA was moderately toxic to *D. magna* (48-h EC50 was 10 mg/l) according to the current U.S. EPA acute toxicity evaluation standard, and it was weakly oestrogenic with 5 orders of magnitude lower activity than that of the natural estrogen 17 beta-oestradiol in the yeast screen, while no mutagenicity was observed. All seven BPs tested here showed moderate to slight acute toxicity, no mutagenicity, and weak oestrogenic activity as well as BPA. Some of the BPs showed considerably higher oestrogenic activity than BPA, and others exhibited much lower activity. Bisphenol S (bis(4-hydroxydiphenyl)sulfone) and bis(4-hydroxyphenyl)sulfide showed oestrogenic activity.

Biodegradation is a major mechanism for eliminating various environmental pollutants. Studies on the biodegradation of bisphenols have mainly focused on bisphenol A. A number of BPA-degrading bacteria have been isolated from enrichments of sludge from wastewater treatment plants. The first step in the biodegradation of BPA is the hydroxylation of the carbon atom of a methyl group or the quaternary carbon in the BPA molecule. Judging from these features of the biodegradation mechanisms, it is possible that the same mechanism used for BPA is used to biodegrade all bisphenols that have at least one methyl or methylene group bonded at the carbon atom between the two phenol groups. However, bisphenol F ((bis(4-hydroxyphenyl)methane; BPF), which has no substituent at the bridging carbon, is unlikely to be metabolised by such a mechanism. Nevertheless BPF is readily degraded by river water microorganisms under aerobic conditions. From this evidence, it was clear that a specific mechanism for biodegradation of BPF does exist in the natural ecosystem, Algae can enhance the photodegradation of bisphenols. The photodegradation rate of BPF increased with increasing algae concentration. Humic acid and Fe³⁺ ions also enhanced the photodegradation of BPF. The effect of pH value on the BPF photodegradation was also important.

Terrestrial Fate: Bisphenol A has low to moderate mobility to soil and can be biodegraded in the presence of oxygen following acclimation.

Aquatic Fate: When released in water, bisphenol A can undergo biodegradation and may be adsorb to suspended solids and sediments.

Atmospheric Fate: Bisphenol A in air will exist in the particulate phase and may be removed from the atmosphere through dry deposition or photolysis.

Ecotoxicity: Toxicity tests show that bisphenol A is moderately toxic to aquatic organisms.

Fish LC50 (96 h): 42 mg/l

DO NOT discharge into sewer or waterways.

Persistence and degradability

| Ingredient | Persistence: Water/Soil | Persistence: Air |
|-------------|-----------------------------|-----------------------------|
| bisphenol A | HIGH (Half-life = 360 days) | LOW (Half-life = 0.31 days) |
| phenol | LOW (Half-life = 10 days) | LOW (Half-life = 0.95 days) |

Bioaccumulative potential

| Ingredient | Bioaccumulation |
|-------------|-----------------|
| bisphenol A | LOW (BCF = 100) |

| Ingredient | Bioaccumulation |
|------------|------------------|
| phenol | LOW (BCF = 17.5) |

Mobility in soil

| Ingredient | Mobility |
|-------------|-------------------|
| bisphenol A | LOW (KOC = 75190) |
| phenol | LOW (KOC = 268) |



SECTION 13 Disposal considerations

Waste treatment methods

| | |
|-------------------------------------|--|
| Product / Packaging disposal | <ul style="list-style-type: none"> ▶ Containers may still present a chemical hazard/ danger when empty. ▶ Return to supplier for reuse/ recycling if possible. <p>Otherwise:</p> <ul style="list-style-type: none"> ▶ If container can not be cleaned sufficiently well to ensure that residuals do not remain or if the container cannot be used to store the same product, then puncture containers, to prevent re-use, and bury at an authorised landfill. ▶ Where possible retain label warnings and SDS and observe all notices pertaining to the product. <p>Legislation addressing waste disposal requirements may differ by country, state and/ or territory. Each user must refer to laws operating in their area. In some areas, certain wastes must be tracked.</p> <p>A Hierarchy of Controls seems to be common - the user should investigate:</p> <ul style="list-style-type: none"> ▶ Reduction ▶ Reuse ▶ Recycling ▶ Disposal (if all else fails) <p>This material may be recycled if unused, or if it has not been contaminated so as to make it unsuitable for its intended use. Shelf life considerations should also be applied in making decisions of this type. Note that properties of a material may change in use, and recycling or reuse may not always be appropriate. In most instances the supplier of the material should be consulted.</p> <ul style="list-style-type: none"> ▶ DO NOT allow wash water from cleaning or process equipment to enter drains. ▶ It may be necessary to collect all wash water for treatment before disposal. ▶ In all cases disposal to sewer may be subject to local laws and regulations and these should be considered first. ▶ Where in doubt contact the responsible authority. |
|-------------------------------------|--|

SECTION 14 Transport information

Labels Required

| | |
|-------------------------|---|
| |  |
| Marine Pollutant |  |

Land transport (DOT)

| | | |
|-------------------------------------|---|---|
| UN number | 3077 | |
| UN proper shipping name | Environmentally hazardous substance, solid, n.o.s. (contains bisphenol A) | |
| Transport hazard class(es) | Class | 9 |
| | Subrisk | Not Applicable |
| Packing group | III | |
| Environmental hazard | Environmentally hazardous | |
| Special precautions for user | Hazard Label | 9 |
| | Special provisions | 8, 146, 335, 384, A112, B54, B120, IB8, IP3, N20, N91, T1, TP33 |

For Individual Packages of Environmentally Hazardous Substances meeting the descriptions of UN 3077 or UN 3082 that contain LESS THAN the reportable quantity (5000 lbs) - Not Regulated

For Individual Packages of Environmentally Hazardous Substances meeting the descriptions of UN 3077 or UN 3082 that contain MORE THAN the reportable quantity (5000 lbs) - Regulated and classified as below:

Air transport (ICAO-IATA / DGR)

| | | |
|-----------------------------------|---|----------------|
| UN number | 3077 | |
| UN proper shipping name | Environmentally hazardous substance, solid, n.o.s. * (contains bisphenol A) | |
| Transport hazard class(es) | ICAO/IATA Class | 9 |
| | ICAO / IATA Subrisk | Not Applicable |
| | ERG Code | 9L |

| | | |
|-------------------------------------|---|-------------------------|
| Packing group | III | |
| Environmental hazard | Environmentally hazardous | |
| Special precautions for user | Special provisions | A97 A158 A179 A197 A215 |
| | Cargo Only Packing Instructions | 956 |
| | Cargo Only Maximum Qty / Pack | 400 kg |
| | Passenger and Cargo Packing Instructions | 956 |
| | Passenger and Cargo Maximum Qty / Pack | 400 kg |
| | Passenger and Cargo Limited Quantity Packing Instructions | Y956 |
| | Passenger and Cargo Limited Maximum Qty / Pack | 30 kg G |

Sea transport (IMDG-Code / GGVSee)

| | | |
|-------------------------------------|---|---------------------|
| UN number | 3077 | |
| UN proper shipping name | ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (contains bisphenol A) | |
| Transport hazard class(es) | IMDG Class | 9 |
| | IMDG Subrisk | Not Applicable |
| Packing group | III | |
| Environmental hazard | Marine Pollutant | |
| Special precautions for user | EMS Number | F-A , S-F |
| | Special provisions | 274 335 966 967 969 |
| | Limited Quantities | 5 kg |

Transport in bulk according to Annex II of MARPOL and the IBC code

Not Applicable

Transport in bulk in accordance with MARPOL Annex V and the IMSBC Code

| Product name | Group |
|---------------------------------|---------------|
| bisphenol A | Not Available |
| 2,4'-(1-methylethylidene)phenol | Not Available |
| phenol | Not Available |

Transport in bulk in accordance with the ICG Code

| Product name | Ship Type |
|---------------------------------|---------------|
| bisphenol A | Not Available |
| 2,4'-(1-methylethylidene)phenol | Not Available |
| phenol | Not Available |

SECTION 15 Regulatory information

Safety, health and environmental regulations / legislation specific for the substance or mixture

bisphenol A is found on the following regulatory lists

| | |
|--|--|
| Chemical Footprint Project - Chemicals of High Concern List | US EPCRA Section 313 Chemical List |
| US - California - Biomonitoring - Priority Chemicals | US NIOSH Recommended Exposure Limits (RELs) |
| US - California Proposition 65 - Maximum Allowable Dose Levels (MADLs) for Chemicals Causing Reproductive Toxicity | US OSHA Permissible Exposure Limits (PELs) Table Z-1 |
| US - California Proposition 65 - Reproductive Toxicity | US OSHA Permissible Exposure Limits (PELs) Table Z-3 |
| US - California Safe Drinking Water and Toxic Enforcement Act of 1986 - Proposition 65 List | US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory |
| US - Massachusetts - Right To Know Listed Chemicals | US TSCA Chemical Substance Inventory - Interim List of Active Substances |
| US DOE Temporary Emergency Exposure Limits (TEELs) | US TSCA Section 4/12 (b) - Sunset Dates/Status |
| US EPA Integrated Risk Information System (IRIS) | |

2,4'-(1-methylethylidene)phenol is found on the following regulatory lists

| | |
|--|---|
| US List of Active Substances Exempt from the TSCA Inventory Notifications (Active-Inactive) Rule | US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory |
|--|---|

phenol is found on the following regulatory lists

| | |
|---|--|
| International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs | US DOE Temporary Emergency Exposure Limits (TEELs) |
| US - California Hazardous Air Pollutants Identified as Toxic Air Contaminants | US EPA Integrated Risk Information System (IRIS) |
| US - Massachusetts - Right To Know Listed Chemicals | US EPCRA Section 313 Chemical List |
| US ACGIH Threshold Limit Values (TLV) | US NIOSH Recommended Exposure Limits (RELs) |
| US ACGIH Threshold Limit Values (TLV) - Carcinogens | US OSHA Permissible Exposure Limits (PELs) Table Z-1 |
| US ATSDR Minimal Risk Levels for Hazardous Substances (MRLs) | US SARA Section 302 Extremely Hazardous Substances |
| US Clean Air Act - Hazardous Air Pollutants | US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory |
| US CWA (Clean Water Act) - List of Hazardous Substances | US TSCA Chemical Substance Inventory - Interim List of Active Substances |
| US CWA (Clean Water Act) - Priority Pollutants | US TSCA Section 4/12 (b) - Sunset Dates/Status |
| US CWA (Clean Water Act) - Toxic Pollutants | |

Federal Regulations

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Section 311/312 hazard categories


| | |
|--|-----|
| Flammable (Gases, Aerosols, Liquids, or Solids) | No |
| Gas under pressure | No |
| Explosive | No |
| Self-heating | No |
| Pyrophoric (Liquid or Solid) | No |
| Pyrophoric Gas | No |
| Corrosive to metal | No |
| Oxidizer (Liquid, Solid or Gas) | No |
| Organic Peroxide | No |
| Self-reactive | No |
| In contact with water emits flammable gas | No |
| Combustible Dust | No |
| Carcinogenicity | No |
| Acute toxicity (any route of exposure) | No |
| Reproductive toxicity | Yes |
| Skin Corrosion or Irritation | No |
| Respiratory or Skin Sensitization | Yes |
| Serious eye damage or eye irritation | Yes |
| Specific target organ toxicity (single or repeated exposure) | No |
| Aspiration Hazard | No |
| Germ cell mutagenicity | No |
| Simple Asphyxiant | No |
| Hazards Not Otherwise Classified | No |

US. EPA CERCLA Hazardous Substances and Reportable Quantities (40 CFR 302.4)

| Name | Reportable Quantity in Pounds (lb) | Reportable Quantity in kg |
|--------|------------------------------------|---------------------------|
| phenol | 1000 | 454 |

State Regulations

US. California Proposition 65

 **WARNING:** This product can expose you to chemicals including **bisphenol A**, which is known to the State of California to cause birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov.

National Inventory Status

| National Inventory | Status |
|---|---|
| Australia - AIIC / Australia Non-Industrial Use | Yes |
| Canada - DSL | Yes |
| Canada - NDSL | No (bisphenol A; 2,4'-(1-methylethylidene)phenol; phenol) |
| China - IECSC | Yes |
| Europe - EINEC / ELINCS / NLP | Yes |
| Japan - ENCS | No (2,4'-(1-methylethylidene)phenol) |
| Korea - KECI | No (2,4'-(1-methylethylidene)phenol) |
| New Zealand - NZIoC | Yes |
| Philippines - PICCS | Yes |
| USA - TSCA | Yes |
| Taiwan - TCSI | Yes |
| Mexico - INSQ | No (2,4'-(1-methylethylidene)phenol) |

| National Inventory | Status |
|--------------------|--------|
| Vietnam - NCI | Yes |
| Russia - FBEPH | Yes |

Legend: Yes = All CAS declared ingredients are on the inventory
No = One or more of the CAS listed ingredients are not on the inventory. These ingredients may be exempt or will require registration.

SECTION 16 Other information

| | |
|---------------|------------|
| Revision Date | 15/04/2021 |
| Initial Date | 17/05/2005 |

SDS Version Summary

| Version | Date of Update | Sections Updated |
|------------|----------------|--|
| 10.1.2.1 | 16/08/2016 | Acute Health (eye), Acute Health (inhaled), Acute Health (skin), Acute Health (swallowed), Chronic Health, Classification, Disposal, Environmental, Exposure Standard, Fire Fighter (fire/explosion hazard), Spills (major), Spills (minor), Storage (storage incompatibility), Toxicity and Irritation (Other), Transport, Transport Information, Use |
| 11.1.2.1 | 14/04/2021 | Expiration. Review and Update |
| 11.1.3.1 | 10/05/2021 | Regulation Change |
| 11.1.4.1 | 24/05/2021 | Regulation Change |
| 11.1.4.2 | 30/05/2021 | Template Change |
| 11.1.4.3 | 04/06/2021 | Template Change |
| 11.1.4.4 | 05/06/2021 | Template Change |
| 11.1.4.5 | 09/06/2021 | Template Change |
| 11.1.4.6 | 11/06/2021 | Template Change |
| 11.1.4.7 | 14/06/2021 | Template Change |
| 11.1.4.8 | 05/07/2021 | Template Change |
| 11.1.5.8 | 14/07/2021 | Regulation Change |
| 11.1.6.8 | 15/07/2021 | Regulation Change |
| 11.1.6.9 | 01/08/2021 | Template Change |
| 11.1.7.9 | 02/08/2021 | Regulation Change |
| 11.1.8.9 | 05/08/2021 | Regulation Change |
| 11.1.9.9 | 09/08/2021 | Regulation Change |
| 11.1.10.9 | 16/08/2021 | Regulation Change |
| 11.1.10.10 | 29/08/2021 | Template Change |
| 11.1.11.10 | 30/08/2021 | Regulation Change |
| 11.1.12.10 | 06/09/2021 | Regulation Change |
| 11.1.13.10 | 13/09/2021 | Regulation Change |
| 11.1.13.11 | 16/09/2021 | Template Change |
| 11.1.14.11 | 16/09/2021 | Regulation Change |
| 11.1.15.11 | 23/09/2021 | Regulation Change |
| 11.1.15.12 | 30/09/2021 | Template Change |

Other information

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

The SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

Definitions and abbreviations

PC—TWA: Permissible Concentration-Time Weighted Average
 PC—STEL: Permissible Concentration-Short Term Exposure Limit
 IARC: International Agency for Research on Cancer
 ACGIH: American Conference of Governmental Industrial Hygienists
 STEL: Short Term Exposure Limit
 TEEL: Temporary Emergency Exposure Limit.
 IDLH: Immediately Dangerous to Life or Health Concentrations
 ES: Exposure Standard
 OSF: Odour Safety Factor
 NOAEL :No Observed Adverse Effect Level
 LOAEL: Lowest Observed Adverse Effect Level
 TLV: Threshold Limit Value
 LOD: Limit Of Detection
 OTV: Odour Threshold Value
 BCF: BioConcentration Factors
 BEI: Biological Exposure Index
 AIIC: Australian Inventory of Industrial Chemicals
 DSL: Domestic Substances List

NDSL: Non-Domestic Substances List
IECSC: Inventory of Existing Chemical Substance in China
EINECS: European INventory of Existing Commercial chemical Substances
ELINCS: European List of Notified Chemical Substances
NLP: No-Longer Polymers
ENCS: Existing and New Chemical Substances Inventory
KECI: Korea Existing Chemicals Inventory
NZIoC: New Zealand Inventory of Chemicals
PICCS: Philippine Inventory of Chemicals and Chemical Substances
TSCA: Toxic Substances Control Act
TCSI: Taiwan Chemical Substance Inventory
INSQ: Inventario Nacional de Sustancias Químicas
NCI: National Chemical Inventory
FBEPH: Russian Register of Potentially Hazardous Chemical and Biological Substances

This document is copyright.

Apart from any fair dealing for the purposes of private study, research, review or criticism, as permitted under the Copyright Act, no part may be reproduced by any process without written permission from CHEMWATCH.

TEL (+61 3) 9572 4700.